Package: LassoNet (via r-universe)

October 13, 2026

Type Package

Title 3CoSE Algorithm

Version 0.8.3

Date 2019-12-17

Author Jonas Striaukas [aut, trl, cre] and Matthias Weber [aut]

Maintainer Jonas Striaukas <jonas.striaukas@gmail.com>

Description Contains functions to estimate a penalized regression model using 3CoSE algorithm, see Weber, Striaukas, Schumacher Binder (2018) <doi:10.2139/ssrn.3211163>.

License GPL (>= 2)

Imports Rcpp (>= 0.11.5)

Suggests snowfall

LinkingTo Rcpp

NeedsCompilation yes

Repository https://jstriaukas.r-universe.dev

Date/Publication 2020-01-19 14:30:08 UTC

RemoteUrl https://github.com/cran/LassoNet

RemoteRef HEAD

RemoteSha 6206114474383876b0762f64d22155362ff46d44

Contents

LassoNet-package 2
beta.update.net 3
betanew_lasso_cpp 4
fastols 5
get.BxBy 6
get.signs.M 7
get.xi 7
lasso.net.fixed 8

lasso.net.grid 9
mat.to.laplacian 11
matrix.M.update 12
soft.thresh 13

Index **14**

`LassoNet-package` *LassoNet: package for 3CoSE algorithm.*

Description

LassoNet contains functions to estimate a penalized regression model using 3CoSE algorithm described in the paper Weber, Striaukas, Schumacher and Binder (2018). The main function of the package is the function lasso.net.grid, see the example below.

Details

Package:	LassoNet
Type:	Package
Version:	0.8.3
Date:	2019-12-16
License:	Open source

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

See Also

`Rcpp`, `glmnet`

`beta.update.net` *Updates β coefficients.*

Description

This function updates β for given penalty parameters.

Usage

```
beta.update.net(x,y,beta,lambda1,lambda2,M1,n.iter,iscpp,tol)
```

Arguments

`x`	input data matrix of size $n \times p$; n - number of observations; p - number of covariates
`y`	response vector or size $n \times 1$
`beta`	initial value for β; default - zero vector of size $n \times 1$
`lambda1`	lasso penalty parameter
`lambda2`	network penalty parameter
`M1`	penalty matrix
`n.iter`	maximum number of iterations for β step; default - 1e5
`iscpp`	binary choice for using cpp function in coordinate updates; 1 - use C++ (default), 0 - use R
`tol`	convergence tolerance level; default - 1e-6

Details

Updates the coefficient vector β given the data and penalty parameters $\lambda 1$ and $\lambda 2$. Convergence criterion is defined as $\sum_{i=1}^{p} |\beta_{i,j} - \beta_{i,j-1}| \leq$ to.

Value

`beta`	updated β vector
`convergence`	binary variable; 1 - yes
`steps`	number of steps until convergence

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p<-200
n<-100
beta.0=array(1,c(p,1))
x<-matrix(rnorm(n*p),n,p)
y<-rnorm(n,mean=0,sd=1)
lambda1<-1
lambda2<-1
M1<-diag(p)
updates<-beta.update.net(x, y, beta.0, lambda1, lambda2, M1)
```

`betanew_lasso_cpp` *C++ subroutine that updates β coefficients.*

Description

This function updates β for given penalty parameters.

Usage

```
betanew_lasso_cpp(xx, xy, beta, M, y, Lambda1, Lambda2, iter, tol)
```

Arguments

`xx`	Bx matrix
`xy`	By vector
`beta`	initial value for β; default - zero vector of size $p \times 1$
`M`	penalty matrix
`y`	response vector or size $n \times 1$
`Lambda1`	lasso penalty parameter
`Lambda2`	network penalty parameter
`iter`	maximum number of iterations for β step
`tol`	convergence tolerance level

Details

See beta.update.net

Value

`beta`	updated β vector
`steps`	number of steps until convergence

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p<-200
n<-100
beta.0=array(1,c(p,1))
x<-matrix(rnorm(n*p),n,p)
y<-rnorm(n,mean=0,sd=1)
lambda1<-1
lambda2<-1
M1<-diag(p)
updates<-beta.update.net(x, y, beta.0, lambda1, lambda2, M1)
```

`fastols` *Fast least squares estimate.*

Description

Computes least squares estimate in an efficient way.

Usage

```
fastols(y, x)
```

Arguments

y	dependent variable
x	response variable

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

Examples

```
p<-10
n<-100
x<-matrix(rnorm(n*p),n,p)
beta<-array(5, c(p,1))
y<-x%*%beta + rnorm(n,mean=0,sd=0.1)
fastols(y,x)
```

get.BxBy *Computes decomposition elements.*

Description

Computes matrices B_X^{ij} and B_y^{ij} to speed up estimation of connection signs. These matrices are stored only for indices that have non zero entries in penalty matrix M.

Usage

```
get.BxBy(x, y, M)
```

Arguments

x	Input data matrix of size $n \times p$, n - number of observations, p - number of covariates
y	y Response vector or size $n \times 1$
M	penalty matrix

Details

Calculates matrices all for i and j indices that have non zero values in a given penalty matrix.

Value

Bx	array of B_X^{ij} stored matrices. $Bx[,,k]$ are the k-th combination of i and j non zero entry in the penalty matrix M
By	array of B_y^{ij} stored matrices. $By[,k]$ are the k-th combination of i and j non zero entry in the penalty matrix M

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p<-200
n<-100
x<-matrix(rnorm(n*p),n,p)
y<-rnorm(n,mean=0,sd=1)
M<-diag(p)
get.BxBy(x, y, M)
```

`get.signs.M` *Vetorizes connection sign matrix.*

Description

Stores a matrix of connection signs to a vector.

Usage

```
get.signs.M(MAT)
```

Arguments

`MAT`	matrix of connection signs that contains -1, 1 or 0

Value

`vec.out`	vectorized MAT matrix

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

`get.xi` *Updates the estimates of the connection signs by running mini OLS models.*

Description

Updates connection signs $\hat{\xi}$.

Usage

```
get.xi(Bx,By,beta,xi,M)
```

Arguments

`Bx`	Bx element
`By`	By element
`beta`	$\hat{\beta}$ estimated value
`xi`	$\hat{\xi}$ matrix estimated at the previous step
`M`	penalty matrix

Value

`xi`	$\hat{\xi}$ matrix

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

`lasso.net.fixed` *Estimates coefficients over the grid values of penalty parameters.*

Description

See lasso.net.grid

Usage

```
lasso.net.fixed(x,y,beta.0,lambda1,lambda2,M1,n.iter,iscpp,tol)
```

Arguments

`x`	$n \times p$ input data matrix
`y`	response vector or size $n \times 1$
`beta.0`	initial value for β; default - zero vector of size $n \times 1$
`lambda1`	lasso penalty coefficient
`lambda2`	network penalty coefficient
`M1`	penalty matrix
`n.iter`	maximum number of iterations for β updating; default - 1e5
`iscpp`	binary choice for using cpp function in coordinate updates; 1 - use C++ (default), 0 - use R.
`tol`	convergence in β tolerance level; default - 1e-6

Details

Function loops through the grid of values of penalty parameters $\lambda 1$ and $\lambda 2$ until convergence is reached. Warm starts are stored for each iterator. The warm starts are stored once the coordinate updating converges.

Value

`beta`	Matrix of β coefficients. Columns denote different $\lambda 1$ coefficients, rows - $\lambda 2$ coefficients
`mse`	Mean squared error value
`iterations`	matrix with stored number of steps for sign matrix to converge
`update.steps`	matrix with stored number of steps for β updates to converge. (only stores the last values from connection signs iterations)
`convergence.in.grid`	matrix with stored values for convergence in β coefficients. If at least one β did not converge in sign matrix iterations, 0 (false) is stored, otherwise 1 (true)

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p=200
n=100
beta.0=array(1,c(p,1))
x=matrix(rnorm(n*p),n,p)
y=rnorm(n,mean=0,sd=1)
lambda1=c(0,1)
lambda2=c(0,1)
M1=diag(p)
lasso.net.fixed(x, y, beta.0, lambda1, lambda2, M1)
```

---

lasso.net.grid *Estimates coefficients and connection signs over the grid of values of penalty parameters λ1 and λ2.*

Description

Fits network regressions over the grid of values of penalty parameters $\lambda 1$ and $\lambda 2$, stores connection signs, number of iterations until convergence and convergence outcome.

Usage

```
lasso.net.grid(x,y ,beta.0,lambda1,lambda2,M1,m.iter,n.iter,iscpp=TRUE,tol,alt.num)
```

Arguments

x	$n \times p$ input data matrix
y	response vector or size $n \times 1$
beta.0	initial value for β. default - zero vector of size $n \times 1$
lambda1	lasso penalty coefficient
lambda2	network penalty coefficient
M1	penalty matrix
m.iter	maximum number of iterations for sign matrix updating; default - 100
n.iter	maximum number of iterations for β updating; default - 1e5
iscpp	binary choice for using cpp function in coordinate updates; 1 - use C++ (default), 0 - use R
tol	convergence in β tolerance level; default - 1e-6
alt.num	alt.num remaining iterataions are stored; default - 12

Details

Fits network regression for the grid values of $\lambda 1$ and $\lambda 2$ using warm starts.

Value

beta	matrix of β coefficients, columns are for different $\lambda 1$ parameters, rows $\lambda 2$ parameters
mse	mean squared error value
M	array of connection signs. $M[, , i, j]$ is the connection sign matrix for j-th $\lambda 1$ value and i-th $\lambda 2$ value
iterations	matrix with stored number of steps for sign matrix to converge
update.steps	matrix with stored number of steps for β updates to converge. (only stores the last values from connection signs iterations)
convergence.in.M	matrix with stored values for convergence in sign matrix
convergence.in.grid	matrix with stored values for convergence in β coefficients. If at least one β did not converge in sign matrix iterations, 0 (false) is stored, otherwise 1 (true)
xi.conv	array with stored connection signs changes in each iteration
beta.alt	array of coefficient vectors in case connection signs alternate

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p=200
n=100
beta.0=array(1,c(p,1))
x=matrix(rnorm(n*p),n,p)
y=rnorm(n,mean=0,sd=1)
lambda1=c(0,1)
lambda2=c(0,1)
M1=diag(p)
lasso.net.grid(x, y, beta.0, lambda1, lambda2, M1)
```

`mat.to.laplacian` *Computes Laplacian matrix.*

Description

Computes Laplacian matrix.

Usage

```
mat.to.laplacian(M1,type)
```

Arguments

`M1`	$p \times p$ matrix
`type`	Laplacian types: 1) "normalized" (default) - normalized Laplacian, 2) "combinatorial" - combinatorial Laplacian

Value

`L`	Laplacian

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

`matrix.M.update` *Updates connection sign matrix.*

Description

Updates M using relation $(M)_{ij} = -\hat{\xi}_{ij}|(M_1)|_{ij}$.

Usage

```
matrix.M.update(M, xi)
```

Arguments

`M`	penalty matrix
`xi`	estimated $\hat{\xi}_{ij}$ matrix

Details

Updates M

Value

`M`	updated M

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

References

Weber, M., Striaukas, J., Schumacher, M., Binder, H. "Network-Constrained Covariate Coefficient and Connection Sign Estimation" (2018) <doi:10.2139/ssrn.3211163>

Examples

```
p<-100
M<-diag(p)
xi<-matrix(rnorm(p*p), p, p)
matrix.M.update(M,xi)
```

`soft.thresh` *Soft thresholding operator.*

Description

Soft thresholding operator.

Usage

```
soft.thresh(x, kappa)
```

Arguments

`x`	β coordinate
`kappa`	κ value in general or λ_1 for covariance updating

Details

Soft thresholding definition: $S(x, \kappa) = sign(x)(|x| - \kappa)_+$

Value

`x`	value after applying soft thresholding operator

Author(s)

Maintainer: Jonas Striaukas <jonas.striaukas@gmail.com>

Examples

```
kappa<-0.2
x<-0.7
soft.thresh(x, kappa)
```

Index

beta.update.net, 3
betanew_lasso_cpp, 4

fastols, 5

get.BxBy, 6
get.signs.M, 7
get.xi, 7
glmnet, 2

lasso.net.fixed, 8
lasso.net.grid, 9
LassoNet-package, 2

mat.to.laplacian, 11
matrix.M.update, 12

Rcpp, 2

soft.thresh, 13